

TOTEW WET-AREA IBC/TOTE TANK HEATERS

- ▶ **Water resistant design for indoor/outdoor use and in wash-down environments**
- ▶ **Insulated to maximize heat efficiency and heat-up time**
- ▶ **Lightweight and easy to install**
- ▶ **Easy-to-use digital temperature controller**
- ▶ **360° Grounded heating element**
- ▶ **Suitable for a wide range of applications:**
 - Viscosity control
 - Freeze protection
 - Temperature maintenance
 - Heat-up process control



Specifications:

Operating Temperature: Up to 140°F (60°C)

Digital Control: Programmable in °F and °C

Built-in High-limit Safety Thermostat: 185°F (85°C)

Weight:

TOTEW36: 19.0 lbs (8.5 kg)

TOTEW42: 22.5 lbs (10.1 kg)

TOTEW48: 26.0 lbs (11.8 kg)

Material: Extra-durable polyester cloth

Power Cord: 72 in (1.8 m) long

120 V: Standard 3-prong plug (NEMA 5-15)

240 V: Standard 3-prong plug (NEMA 6-15)

Ingress Protection Rating: IP54

Material: Extra-durable polyester/fiberglass cloth



Fully Insulated Design
With Digital Control



Adjustable Nylon Straps
With Buckles



Certified to UL safety standards

Ordering Information:

Part No. 120VAC	Part No. 240VAC	Size gallon (liter)	Heater Height in (mm)	Total Watts
TOTEW361-ADJV	TOTEW362-ADJV	170-250 (640-950)	36 (914)	1440
TOTEW421-ADJV	TOTEW422-ADJV	275 (1000)	42 (1067)	1440
TOTEW481-ADJV	TOTEW482-ADJV	330 (1250)	48 (1219)	1440

European option (240 V only): Replace V with EV at the end of the part number for crimped wire ferrule terminated leads.

Accessories:

Part No.	Description
TOTEW-TOPV	Insulating top cover, minimizes heat loss. Fits all sizes.



Insulating Cover