

# EL-USB-4

## 4-20mA Current Loop USB Data Logger

### ORDERING INFORMATION

|   |               |
|---|---------------|
| Standard Data Logger (Data Logger, Software on CD, Battery) | EL-USB-4      |
| Replacement Battery   | BAT 3V6 1/2AA |

### FEATURES

- 4-20mA current loop measurement range
- Logging rates between 1s and 12hr
- Stores 32,510 readings
- Connection via two screw terminals
- USB interface for set-up and data download
- User-programmable alarm thresholds
- Status indication via red and green LEDs
- Supplied with replaceable internal lithium battery and Windows control software

This standalone data logger measures and stores up to 32,000 current loop readings over a 4-20mA measurement range. The user can easily set up the logging rate and start time, and download the stored data by plugging the data logger into a PC's

USB port and running the purpose designed software under Windows 2000, XP and Vista (32-bit). The data can then be graphed, printed and exported to other applications. The data logger is supplied complete with a long-life lithium battery. Correct functioning of the unit is indicated by a flashing red and green LED. The data logger features a pair of screw terminals and is supplied complete with a set of measurement leads terminating in crocodile clips.



| Specifications                  | Minimum   | Typical | Maximum     | Unit      |
|---------------------------------|-----------|---------|-------------|-----------|
| 4-20mA d.c. measurement range   | 4         |         | 20          | mA d.c.   |
| Internal resolution             |           | 0.05    |             | mA d.c.   |
| Accuracy (overall error)        |           | ±1      |             | % ±1count |
| Logging rate                    | every 1 s |         | every 12 hr | -         |
| Operating temperature range     | -35 (-31) |         | +80 (+176)  | °C (°F)   |
| 1/2AA 3.6V Lithium Battery Life |           | 1*      |             | Year      |

\* depending on ambient temperature, logging rate and use of alarm LEDs.


### EL-WIN-USB (CONTROL SOFTWARE)

EasyLog USB control software is supplied free of charge with each data logger. Easy to install and use, the control software runs under Windows 2000, XP (Home and Professional Editions) & Vista (32-bit). The software is used to set-up the data logger as well as download, graph and export data to Excel.

The software allows the following parameters to be configured:

- Logger name
- Logging rate (1s, 10s, 1m, 5m, 30m, 1hr, 6hr, 12hr)
- High and low alarms
- Start date and start time

The latest version of the control software may be obtained free of charge contact [hcs@hcs77.com](mailto:hcs@hcs77.com)



# EL-USB-4












## 4-20mA Current Loop USB Data Logger

### LED FLASHING MODES

EL-USB-4 features a red and a green LED.

By default hold is disabled. In this mode the red LED will no longer continue to flash after the logged reading has returned to normal from an alarm condition.

Hold can be turned on via the control software. In this mode the red LED that indicates an alarm condition will continue to flash, even after the logged reading has returned to normal. This feature ensures that the user is notified that an alarm level has been exceeded, without the need to download the data from the logger.

|  |   |   |
|--|---|---|
| <br>Green LED      Red LED |    | <b>Green single flash (10 seconds)</b><br>The data logger is currently logging. No alarm.   |
|  |    | <b>Green single flash (20 seconds)</b><br>The data logger is currently logging. No alarm. However, the battery is low and should be replaced before logging important data. |
|  |    | <b>Green single flash (30 seconds)</b><br>The data logger is not currently logging, but is primed to start at a later date and time (delayed start).                        |
|  |  | <b>Green double flash (20 seconds)</b><br>The data logger is full and has stopped logging. No alarm.  |
|  |  | <b>Red single flash (10 seconds)</b><br>The data logger is currently logging. Low alarm.  |
|  |  | <b>Red single flash (20 seconds)</b><br>The data logger is currently logging. Low alarm. However, the battery is low and should be replaced before logging important data.  |
|  |  | <b>Red double flash (10 seconds)</b><br>The data logger is currently logging. High alarm.   |
|  |  | <b>Red double flash (20 seconds)</b><br>The data logger is currently logging. High alarm. However, the battery is low and should be replaced before logging important data. |
|  |  | <b>Red/Green single flash (20 seconds)</b><br>The data logger is full and has stopped logging. Alarm (high, low or both).   |
|  |  | <b>No LEDs flash</b><br>The data logger is stopped, the battery is empty or there is no battery fitted.   |

# EL-USB-4


## 4-20mA Current Loop USB Data Logger

### DIMENSIONS

All dimensions in mm (inches)



### CONNECTION AND APPLICATIONS



# EL-USB-4

## 4-20mA Current Loop USB Data Logger

### BATTERY REPLACEMENT

We recommend that you replace the battery every 12 months, or prior to logging critical data.

The EL-USB-4 does not lose its stored readings when the battery is discharged or when the battery is replaced; however, the data logging process will be stopped and cannot be re-started until the battery has been replaced and the logged data has been downloaded to a PC.

Only use 3.6V 1/2AA lithium batteries. Check with your supplier that the battery you are ordering is 'press fit' and is not fitted with solder tags. Before replacing the battery, remove the EL-USB-4 from the PC.

**Note:**

Leaving the EL-USB-4 plugged into the USB port for longer than necessary will cause some of the battery capacity to be lost.

**WARNING**

Handle lithium batteries carefully, observe warnings on battery casing. Dispose of in accordance with local regulations.

# EL-USB-4

## 4-20mA Current Loop USB Data Logger

### THE EASYLOG USB RANGE

Each EL-USB data logger features the direct-to-USB connection and easy-to-use functionality that the range is known for. The range comprises 14 data loggers as detailed in the following table:

| Part No       | Function   | Range   | Accuracy (overall error) |               | Readings | Battery                     | Battery Life* |
|---------------|--|---|--------------------------|---------------|----------|-----------------------------|---------------|
|               |  |   | Typ.                     | Max.          |          |                             |               |
| EL-USB-1      | Temperature  | -35 to +80 °C (-31 to +176 °F)                | ±1°C (±2°F)              |               | 16,382   | 3.6V ½AA                    | 1 year        |
| EL-USB-1-PRO  | High temperature   | -40 to +125 °C (-40 to +257 °F)               | ±0.2°C (±0.4°F)          | ±0.5°C (±1°F) | 32,510   | 3.6V ¾AA                    | 3 years       |
| EL-USB-2      | Temperature, humidity & dew point                                | -35 to +80 °C (-31 to +176 °F)<br>0 to 100%RH | ±0.5°C (±1°F)            | ±2°C (±4°F)   | 16,382   | 3.6V ½AA                    | 1 year        |
|               |  |   | ±3%RH                    | ±6.0%RH       | 16,382   |                             |               |
| EL-USB-2+     | Increased accuracy temperature, humidity & dew point             | -35 to +80 °C (-31 to +176 °F)<br>0 to 100%RH | ±0.3°C (±0.6°F)          | ±1.5°C (±3°F) | 16,382   | 3.6V ½AA                    | 1 year        |
|               |  |   | ±2.0%RH                  | ±4.0%RH       | 16,382   |                             |               |
| EL-USB-2-LCD  | Temperature, humidity & dew point with LCD                       | -35 to +80 °C (-31 to +176 °F)<br>0 to 100%RH | ±0.5°C (±1°F)            | ±2°C (±4°F)   | 16,379   | 3.6V ½AA                    | 1 year        |
|               |  |   | ±3.0%RH                  | ±6.0%RH       | 16,379   |                             |               |
| EL-USB-2-LCD+ | Increased accuracy temperature, humidity & dew point with LCD    | -35 to +80 °C (-31 to +176 °F)<br>0 to 100%RH | ±0.3°C (±0.6°F)          | ±1.5°C (±3°F) | 16,379   | 3.6V ½AA                    | 1 year        |
|               |  |   | ±2.0%RH                  | ±4.0%RH       | 16,379   |                             |               |
| EL-USB-3      | Voltage  | 0 to 30V d.c.                                 | ±1%                      |               | 32,510   | 3.6V ½AA                    | 1 year        |
| EL-USB-4      | Current loop   | 4 to 20mA                                     | ±1%                      |               | 32,510   | 3.6V ½AA                    | 1 year        |
| EL-USB-TC     | Thermocouple (J, K and T-type)<br>K-type probe included          | -200 to +1350°C (-328 to +2462°F) (K-type)    | ±1°C (±2°F)              |               | 32,510   | 3.6V ½AA                    | 6 months      |
|               |  | -200 to +1190°C (-328 to +2174°F) (J-type)    |                          |               |          |                             |               |
|               |  | -200 to +390°C (-328 to +734°F) (T-type)      |                          |               |          |                             |               |
| EL-USB-TC-LCD | Thermocouple with LCD (J, K and T-type)<br>K-type probe included | -200 to +1350°C (-328 to +2462°F) (K-type)    | ±1°C (±2°F)              |               | 32,510   | 3.6V ½AA                    | 6 months      |
|               |  | -200 to +1190°C (-328 to +2174°F) (J-type)    |                          |               |          |                             |               |
|               |  | -200 to +390°C (-328 to +734°F) (T-type)      |                          |               |          |                             |               |
| EL-USB-C0     | Carbon monoxide  | 0 to 1000ppm <b>NOT A LIFE SAVING DEVICE</b>  | ±6ppm                    |               | 32,510   | 3.6V ½AA                    | 3 months      |
| EL-USB-C0300  | Carbon monoxide  | 0 to 300ppm <b>NOT A LIFE SAVING DEVICE</b>   | ±4ppm                    |               | 32,510   | 3.6V ½AA                    | 3 months      |
| EL-USB-LITE   | Low cost temperature   | -10 °C to +50 °C (+14 to +122 °F)             | ±1°C (±2°F)              |               | 4,080    | CR1620<br>Lithium coin cell | 1 month       |
| EL-USB-RT     | Real-time temperature & humidity monitor                         | -20 to +70 °C (-4 to +158 °F)                 | ±1.5°C (±3°F)            |               | 7 days   | N/A                         | N/A           |
|               |  |   | ±4.5%RH                  |               |          |                             |               |

\*Depending on logging rate, ambient temperature, and use of alarm LED

Heaters Controls & Sensors  
60 Meg dr # 13  
London Ontario N6E 3T6  
Canada  
Tel : 519 686 2715  
Fax : 519 686 8159  
Email : hcs@hcs77.com



www.hcs77.com 519 686 2715

electronics