DHLS

 \cap ΙO


ΡZ


 n R

Your Heating Specialist since 1949

Heavy Duty Mid-Temperature Silicone Rubber Drum and Pail Heaters

Product Highlights







Wide 4" (102mm) silicone rubber band

Patented grounded heating element meets NEC 427.23

Moisture, chemical, and radiation resistant

Heating element is laminated between two layers of 20mil fiberalass reinforced silicone rubber



(see ordering options for details)

Specifications:

- Power Density: 2.50 W/in² (0.39W/cm²) for metal surfaces
- Adjustable thermostat: Up to 160°F (71°C)[†]
- Voltage Options: 120VAC or 240VAC
- Exposure Temperature: -60°F to 450°F (-51°C to 232°C)
- Dielectric Strenath: Over 2000 volts
- Silicone Rubber Density: 46.0 oz/yd² (1560 g/m²)
- Spring closure can be expanded 3" (76mm)
- Power cord 6-foot (1.8m) long 120V includes standard 3-prong plug (NEMA 5-15) 240V has crimped ferrule terminated leads
- Ingress Protection Rating: IP54

4 (102) 30 (114) 18.6 (473) 58.5 (1486) 4 (102)

55 (208)

[†] If precise temperature control is required for your application, please contact BriskHeat or your local distributor for application assistance and product solutions.

Ordering Information:

Size	Watts	Heavy Duty	
Gallon (Liter)		120VAC	240VAC
5 (19)	550	DHLS10	DHLS20*
16 (61)	700	DHLS11	DHLS21*
30 (114)	1000	DHLS13	DHLS23*
55 (208)	1200	DHLS15	DHLS25*


Part Number	Description	
10180	Replacement spring for Silicone Rubber Drum Heaters	

* 240VAC models have crimped wire ferrule terminated leads.

Ordering Options:

CSA/UL Approved Option: Add an "A" at the end of the part number. No plug - has bare wire leads.

HCS Heaters, Controls And Sensors LTD HEATING AND CONTROL SYSTEMS



22.3 (566)

70.0 (1778)

4 (102)