

EL-USB-2

Humidity, Temperature and Dew Point USB Data Logger

ORDERING INFORMATION

| | |
|---|---------------|
| Standard Data Logger (Data Logger, Software on CD, Battery) | EL-USB-2 |
| Replacement Battery | BAT 3V6 1/2AA |

FEATURES

- 0 to 100%RH measurement range
- -35 to +80 °C (-31 to +176 °F) measurement range
- Dew point indication via Windows control software
- USB interface for set-up and data download
- User-programmable alarm thresholds for %RH & T
- Status indication via red and green LEDs
- Supplied with replaceable internal lithium battery and Windows control software
- Environmental protection to IP67



This standalone data logger measures and stores up to 16,382 relative humidity and 16,382 temperature readings over 0 to 100%RH and -35 to +80 °C (-31 to +176 °F) measurement ranges. The user can easily set up the logging rate and start-time,

and download the stored data by plugging the data logger into a PC's USB port and running the purpose designed software under Windows 2000, XP and Vista (32-bit). Relative humidity, temperature and dew point (the temperature at which water vapor present in the air begins to condense) data can then be graphed, printed and exported to other applications. The data logger is supplied complete with a long-life lithium battery, which can typically allow logging for a year. Status indication is via flashing red and green LEDs. The logger is protected against ingress from water and dust to IP67 standard when the plastic cap and seal are fitted.

| Specifications | | Minimum | Typical | Maximum | Unit |
|---------------------------------|----------------------------|------------|-------------|-------------|---------|
| Relative Humidity | Measurement range | 0 | | 100 | %RH |
| | Repeatability (short term) | | ±0.1 | | %RH |
| | Accuracy (overall error) | | ±3.0* | | %RH |
| | Internal resolution | | 0.5 | | %RH |
| | Long term stability | | 0.5 | | %RH/Yr |
| Temperature | Measurement range | -35 (-31) | | +80 (+176) | °C (°F) |
| | Repeatability | | ±0.1 (±0.2) | | °C (°F) |
| | Accuracy (overall error) | | ±0.5 (±1) | ±1.5 (±3) | °C (°F) |
| | Internal resolution | | 0.5 (1) | | °C (°F) |
| Dew Point | Accuracy (overall error) | | ±1.1 (±2)** | | °C (°F) |
| Logging rate | | every 10 s | | every 12 hr | - |
| Operating temperature range | | -35 (-31) | | +80 (+176) | °C (°F) |
| 1/2AA 3.6V Lithium Battery Life | | | 1*** | | Year |

* This specifies the overall error in the logged readings, for relative humidity measurements between 20 and 80%RH.

** This specifies the overall error in the calculated dew point, for relative humidity measurements between 40 and 100%RH at 25 °C.

*** Depending on sample rate, ambient temperature and use of alarm LEDs.

EL-USB-2

Humidity, Temperature and Dew Point USB Data Logger

EL-WIN-USB (CONTROL SOFTWARE)


EasyLog USB control software is supplied free of charge with each data logger. Easy to install and use, the control software runs under Windows 2000, XP (Home and Professional Editions) & Vista (32-bit). The software is used to set-up the data logger as well as download, graph and export data to Excel.

The software allows the following parameters to be configured:

- Logger name
- °C, °F
- Logging rate (10s, 1m, 5m, 30m, 1hr, 6hr, 12hr)
- High and low alarms for humidity and temperature
- Start date and start time


The latest version of the control software may be obtained free of charge from us









email : hcs@hcs77.com



LED FLASHING MODES

EL-USB-2 features 2 bi-colour LEDs; one LED represents temperature measurement, the other represents RH. Each is clearly marked on the logger. To save power, the status indication alternates between the two channels every 10 seconds. First you will see the status of the temperature logging and 10 seconds later you will see the status of the RH logging and so on.



| | | |
|---|---|---|
|  |  | Green double flash The data logger is not currently logging, but is primed to start at a later date and time (delayed start). |
| |  | Green single flash The data logger is currently logging. No alarm on the channel. |
| |  | Red single flash The data logger is currently logging. Low alarm on the channel. |
| |  | Red double flash The data logger is currently logging. High alarm on the channel. |
| |  | Green triple flash The data logger is full and has stopped logging. No alarm on the channel. |
| |  | Red triple flash The data logger is full and has stopped logging. Alarm (high, low or both). |
| |  | No LEDs flash The data logger is stopped, the battery is empty or there is no battery fitted. |

EL-USB-2



Humidity, Temperature and Dew Point USB Data Logger

DIMENSIONS

All dimensions in mm (inches)



MEASUREMENT ACCURACY



BATTERY REPLACEMENT

We recommend that you replace the battery every 12 months, or prior to logging critical data.

The EL-USB-2 does not lose its stored readings when the battery is discharged or when the battery is replaced; however, the data logging process will be stopped and cannot be re-started until the battery has been replaced and the logged data has been downloaded to a PC.

Only use 3.6V 1/2AA lithium batteries. Check with your supplier that the battery you are ordering is 'press fit' and is not fitted with solder tags. Before replacing the battery, remove the EL-USB-2 from the PC.

Note:

Leaving the EL-USB-2 plugged into the USB port for longer than necessary will cause some of the battery capacity to be lost.

WARNING

Handle lithium batteries carefully, observe warnings on battery casing. Dispose of in accordance with local regulations.

EL-USB-2

Humidity, Temperature and Dew Point USB Data Logger

CAUTION

Exposure of the internal sensor to chemical vapours such as those produced by some plastics and foamed materials may interfere with the internal sensor and cause inaccurate readings to be logged, therefore ensure that the logger is used in a ventilated area i.e. air exchange is allowed.

Exposure to extreme conditions or chemical vapours will require the following reconditioning procedure to bring the internal sensor back to calibration state.

80 °C (176 °F) at < 5% RH for 36h (baking) followed by 20-30 °C (70-90 °F) at >74%RH for 48h (re-hydration)

High levels of pollutants may cause permanent damage to the internal sensor.

THE EASYLOG USB RANGE

Each EL-USB data logger features the direct-to-USB connection and easy-to-use functionality that the range is known for. The range comprises 14 data loggers as detailed in the following table:

| Part No | Function | Range | Accuracy (overall error) | | Readings | Battery | Battery Life* |
|---------------|--|---|--------------------------|---------------|----------|-----------------------------|---------------|
| | | | Typ. | Max. | | | |
| EL-USB-1 | Temperature | -35 to +80 °C (-31 to +176 °F) | ±1°C (±2°F) | | 16,382 | 3.6V ½AA | 1 year |
| EL-USB-1-PRO | High temperature | -40 to +125 °C (-40 to +257 °F) | ±0.2°C (±0.4°F) | ±0.5°C (±1°F) | 32,510 | 3.6V ¾AA | 3 years |
| EL-USB-2 | Temperature, humidity & dew point | -35 to +80 °C (-31 to +176 °F) 0 to 100%RH | ±0.5°C (±1°F) | ±2°C (±4°F) | 16,382 | 3.6V ½AA | 1 year |
| | | | ±3%RH | ±6.0%RH | 16,382 | | |
| EL-USB-2+ | Increased accuracy temperature, humidity & dew point | -35 to +80 °C (-31 to +176 °F) 0 to 100%RH | ±0.3°C (±0.6°F) | ±1.5°C (±3°F) | 16,382 | 3.6V ½AA | 1 year |
| | | | ±2.0%RH | ±4.0%RH | 16,382 | | |
| EL-USB-2-LCD | Temperature, humidity & dew point with LCD | -35 to +80 °C (-31 to +176 °F) 0 to 100%RH | ±0.5°C (±1°F) | ±2°C (±4°F) | 16,379 | 3.6V ½AA | 1 year |
| | | | ±3.0%RH | ±6.0%RH | 16,379 | | |
| EL-USB-2-LCD+ | Increased accuracy temperature, humidity & dew point with LCD | -35 to +80 °C (-31 to +176 °F) 0 to 100%RH | ±0.3°C (±0.6°F) | ±1.5°C (±3°F) | 16,379 | 3.6V ½AA | 1 year |
| | | | ±2.0%RH | ±4.0%RH | 16,379 | | |
| EL-USB-3 | Voltage | 0 to 30V d.c. | ±1% | | 32,510 | 3.6V ½AA | 1 year |
| EL-USB-4 | Current loop | 4 to 20mA | ±1% | | 32,510 | 3.6V ½AA | 1 year |
| EL-USB-TC | Thermocouple (J, K and T-type) K-type probe included | -200 to +1350°C (-328 to +2462°F) (K-type) | ±1°C (±2°F) | | 32,510 | 3.6V ½AA | 6 months |
| | | -200 to +1190°C (-328 to +2174°F) (J-type) | | | | | |
| | | -200 to +390°C (-328 to +734°F) (T-type) | | | | | |
| EL-USB-TC-LCD | Thermocouple with LCD (J, K and T-type) K-type probe included | -200 to +1350°C (-328 to +2462°F) (K-type) | ±1°C (±2°F) | | 32,510 | 3.6V ½AA | 6 months |
| | | -200 to +1190°C (-328 to +2174°F) (J-type) | | | | | |
| | | -200 to +390°C (-328 to +734°F) (T-type) | | | | | |
| EL-USB-C0 | Carbon monoxide | 0 to 1000ppm NOT A LIFE SAVING DEVICE | ±6ppm | | 32,510 | 3.6V ½AA | 3 months |
| EL-USB-C0300 | Carbon monoxide | 0 to 300ppm NOT A LIFE SAVING DEVICE | ±4ppm | | 32,510 | 3.6V ½AA | 3 months |
| EL-USB-LITE | Low cost temperature | -10 °C to +50 °C (+14 to +122 °F) | ±1°C (±2°F) | | 4,080 | CR1620 Lithium coin cell | 1 month |
| EL-USB-RT | Real-time temperature & humidity monitor | -20 to +70 °C (-4 to +158 °F) | ±1.5°C (±3°F) | | 7 days | N/A | N/A |
| | | | ±4.5%RH | | | | |

*Depending on logging rate, ambient temperature, and use of alarm LED

Heaters Controls & Sensors Ltd
60 Meg Dr Unit 13 London ontario
Canada N6E 3T6

Ph : 519 686 2715
Fx : 519 686 8159
E : hcs@hcs77.com



www.hcs77.com

electronics